



Technical Data Sheet

dozenstampers.nl
geen succes zonder U

PPA 32 μ Under Surface print

Characteristics

Low initial tack, full adhesion achieved after 24 hours.
 Suitable for frozen food packaging as long as processed above 0°C.

Data	
Adhesion	Low initial tack, full adhesion achieved after 24 hours
Sound	Low-noise
Warranty	1 year
Max. width printing	Tape width
Colours	Clear, white, brown
Number of colours printed	Up to 5 colours
Core diameter	76 mm
Minimum order (50 mm x 66 mtr)	15 boxes = 540 rolls, 10 boxes = 360 rolls for 1 or 2 colour print

Tape material	Tapewidth in mm. From ■ in maximum length possible											Max. length	Max. number of colours	Thickness foil
PPA	-	-	-	19	25	-	38	50	75	-	150	990 mtr	5	32 μ

Application

Technical Data	Unit	
Base		polypropylene film, biaxially oriented
Adhesive		Acrylic water-based
Elongation		150% \pm 10%
Thickness	mm	52 μ \pm 10%
Adhesion to steel	2,3 N/cm	\pm 10%
Tensile strenght	58 N/cm	\pm 10%

Properties

- high tensile strength in longitudinal and cross direction
- high adhesion and holding power
- resistant to diluted acids and alkalies
- heat resistant for short exposure up to about +130° C
- low temperature resistant down to about -30° C after application at room temperature
- easy to unwind
- ecologically beneficial