



Characteristics

Good adhesion, suitable for frozen food packaging as long as processed above 5°C.
 Full-surface and reverse printing possible, but is not recommended.

Data	
Adhesion	High initial tack
Sound	Noisy
Warranty	positive printing
	Bleed diapositive printed / coloured
Max. width printing	Tape width minus 2 mm
Colours	Clear, white, brown
Number of colours printed	Up to 5 colours and full colour
Core diameter	76 mm (also possible 3M core diameter 50 mm)
Minimum order (50 mm x 66 mtr)	4 boxes = 144 rolls

Tape material	Tapewidth in mm. From ■ in maximum length possible											Max. length	Max. number of colours	Thickness foil
	-	-	-	19	25	-	38	50	75	100	150			
PPH white	-	-	-	19	25	-	38	50	75	100	150	1500 mtr	5	28μ
PPH clear	-	-	-	19	25	-	38	50	75	100	150	990 mtr	5	28μ
PPH brown	-	-	-	19	25	-	38	50	75	100	150	990 mtr	5	28μ



Application

Technical Data	Unit	
Base		polypropylene film, biaxially oriented
Adhesive		Synthetical Rubber Resin
Elongation at break		140%
Thickness	mm	45 μ \pm 10%
Adhesion to steel	4,0 N/cm	\pm 10%
Tensile strenght	50 N/cm	\pm 10%

Properties

- high tensile strength in longitudinal and cross direction
- high adhesion and holding power
- resistant to diluted acids and alkalies
- heat resistant for short exposure up to about +130° C
- low temperature resistant down to about -30° C after application at room temperature
- easy to unwind
- ecologically beneficial